ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)


Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF COST FOR CONSTRUCTION OF FALSE CEILING AND WALL FINISHING IN ENTRANCE HALL AT D.A.V PUBLIC SCHOOL,AURANGABAD, BIHAR

Ref no


| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|-----------|--|----------|--------|------|--------|
| | | AREA | 498.0 | | SQFT | |
| | | FALSE CEILING | 498.0 | | SQFT | |
| 1 | 12.82 | Providing and fixing at all height false ceiling of 12.5 mm thick -tapered edge gypsum board conforming to IS : 2095 including - providing and fixing as per specification and mention in SOR. (EXCLUDING PAINTING) | 46.3 | | Sq m | |
| 2 | NA | LED AT LIGHT POINTS (UNIT WISE) (inclusive of wire and wiring) | 18.0 | | each | |
| 3 | NA | Diffused light of approximate length (desired colour and brand) | 25.0 | | m | |
| 4 | NA | Electrical work and fitings per light | 18.0 | | each | |
| 5 | NA | fixtures like switch board and other miscellaneous charges | | lumsum | | |
| | | INTERIOR PAINTING AND FINISH (INCLUDING WALL AND CEILING BOTH) | | | | |
| 6 | 13.74 | Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete | 153 | | sqm | |
| 7 | 13.80 A.1 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | 153 | | sqm | |
| 8 | 13.48.1 | Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications. Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of special primer applied @ 0.75 ltr /10 sqm. | 153 | | SqM | |
| 9 | na | Providing and applying <u>Wall paper</u> of approved colour and brand to enhance certain corners and spaces | 50 | | SqM | |
| | | | | TOTAL | | |





РЯОРИСЕР ВУ АМ АИТОРЕЗК ЕРИСАТІОИАL РЯОРИСТ





ГООДОНЧАНОПАООЦА ХАДОГОА НА ТА ОНООНЧ

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- 1st floor , Lalit Bhawan , Opp Dhoop Factory , New Godown , Gaya - 823001 (Bihar)

Mob. No. 7739269750, 09776824147 / Email : happyandassociate@gmail.com, sinha.prashant100@gmail.com

Ref No.....

Date.....


ABSTRACT OF COST OF WALL DÉCOR AND ALUMINUM DOOR IN ENTRANCE HALL AT D A V PUBLIC SCHOOL, AURANGABAD, BIHAR

| S.NO | S.O.R | DESCRIPTION | Qty. | Rate | UNIT | Amount |
|------|---------|--|------|--------|------|--------|
| | | CLOSING AND PLASTERING EXISTING WINDOW AND OPENINGS | | | | |
| 1 | 15.13.2 | Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 meters lead. Of area beyond 3 sqm | 3 | | each | |
| 2 | 6.1.14A | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1:6 (1 cement: 6 coarse sand) | | | CUM | |
| | 6.3A | Extra for Brick work in superstructure above plinth level upto floor V cum | | | CUM | |
| | | | 2.5 | 0 | CUM | |
| 3 | 13.11.4 | Cement plaster in course sand 12 mm cement plaster of mix: 1:6(1 cement: 6 coarse sand) | 10 | | sqm | |
| | | COVERING UP EXISTING MARBLE SLABS | | | | |
| 4 | 9.157.1 | Providing and fixing Pre-laminated medium density fibre board IS: 14587:1998 marked, with one side decorative lamination other side balancing lamination Grade-I(exterior grade) in shelves with screws and fittings wherever required, edges to be sealed with PVC edge bending tape 2.00 mm thick of approved brand (fittings to be paid separately). Pre-laminated with decorative lamination one side and other side balancing lamination exterior Grade - I MDF Board 18 mm thick confirming to IS:14587 | 6.0 | | sqm | |
| 5 | NA | ADHESIVE | 5.0 | | kg | |
| | | LIGHTING AND FIXTURES ON WALL | | | | |
| 6 | NA | LED AT LIGHT POINTS (UNIT WISE) | 18.0 | | each | |
| 7 | NA | Diffused light of approximate length (desired colour and brand) | 49.0 | | m | |
| 8 | NA | Electrical work and fitings per light | 18.0 | | each | |
| 9 | NA | wiring and other fixtures | | lumsum | | |

| | | ALUMINUM DOOR WORK | | | | |
|----|--------|--|------|-------|------|--|
| 10 | 21.2.2 | Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-chargePre-laminated particle board with decorative lamination on both sides (FOR 2 DOORS) | | | | |
| | | 8'6" X 7' | 12.0 | | Sq m | |
| 11 | 21.3.2 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness(weight not less than 12.50 kg/sgm) | 12.0 | | sqm | |
| 12 | N A | Miscellenous items and other fitting and fixture charges | | L.S | | |
| | | | | TOTAL | | |

TOTAL - 1,17,500/- ONLY ONE LAKH SEVENTEEN THOUSAND FIVE HUNDRED ONLY

Note : Rates are inclusive of G.S.T.



ز

PRODUCED BY AN AUTODESK EDUCATIONAL PRODUCT

1

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF ESTIMATE FOR CONSTRUCTION OF WAITING AREA INFRONT OF FEE OFFICE AT DAV PUBLIC SCHOOL, AURANGABAD

Ref no DAV-HA-295

Date - 10.11.2022

| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|----------|---|----------|------|--------------|--------|
| | | WAITING LOBBY AREA | 151.0 | | SQFT | |
| 1 | 2.8.1 | Earth work in excavation in foundation trenches or drains(not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All Kinds of soil | 8.2 | | Cu m | |
| 2 | 2.28 | Supplying and filling in plinth with Local sand including watering, ramming, consolidating and dressing complete | 6.9 | | Cu m | |
| 3 | 11.72 | Providing designation 100A one brick flat | 18.9 | | Sq m | |
| 4 | 5.1.3 | soling joints filled with local sand complete Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring,shuttering,finishing and reinforcement-All work puto plinth level 1:2:4 (1 cement:2 coarse sand:4 graded stone aggregate 20 rr,m nominal size) | 2.0 | | | |
| 5 | 4.1.3 | Providing PCC (1:2:4) with graded Stone chips of 20 mm nominal size excluding the cost of centring and shuttering all works in Foundation all complete | 1.5 | | Cu m | |
| 6 | 5.2.3 | Reinforced cement concrete work in wall (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. upt floor five level excluding cost of centring, shuttering, finishin and reinforcement. 1:2:4(1 cement :2 coarse sand:4 graded stone aggregate 20 mm nominal size) | 1.2 | | C <u>u M</u> | |
| 7 | 5.3 | Reinforced cement conrete work in beams,suspended floors, roofs having slope upto 15, landings,balconiec, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases upto floor five level excludingthe cost of centring, shuttering, finishing and reinforement with 1:2:4(1 cement:2 coarse sand:4 graded stone aggregate 20 mm nominal size). Reinforcement for R.C.C. work including | 2.9 | | Cu M | |
| 8 | 5.22 | straightening, cutting, bending, placing in position and binding all complete. | | | | |
| | 5.22.7D | Thermo-Mechanically Treated bars TMT Fe- 500-I6mrn dia. | 253.0 | | | 0 |
| | 5.22.7C | Thermo-Mechanically Treated bars TMTC-500- 12mm dia. | 315.0 | | KG | 0 |
| | 5.22.7A | Thermo-Mechanically Treated bars TMTC-500- 8mm dia. | 330.0 | | | 0 |
| 9 | 6.1.12/1 | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1 .:4 (1 cement: 4 coarse sand) | 2.8 | | Cu m | 0 |
| 10 | 13.11.4 | 12 mm (1:6) cement Plaster (Toilet wall) | 26.0 | | Sq m | 0 |

| 11 | 11.41.2 | Providing and laying vitrifed floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS : 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching pigments etc., complete. Size of Tile 60x60 cm | 14.8 | Sqm | |
|----|---------|---|------|--------------|--|
| 12 | 8.2.2.2 | Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations, of required size,approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement : 4coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups,including rubbing, curing, moulding and polishing to edges to give high gloss finish etc. complete at all levels. Granite of any colour and shade Area of slab over 0.50 sqm | 1.1 | sqm | |
| 13 | 13.78.1 | Providing one coat of cement primer of approved brand and manufacture on wall surface all complete | 26.0 | Sq m | |
| 14 | 13.79.1 | Providing water proof cement paint of approved brand and manufacture and of required shade to give and even shade three or more coat on new work all complete | 26.0 | Sq m | |
| 15 | 21.2.2 | Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-chargePre-laminated particle board with decorative lamination on both sides | 5.2 | Sq m | |
| 16 | 26.4 | Providing and fixing hard drawn steel wire fabric of size 75 x25 mm mesh or other suitable size wire mesh to be fixed & firmly anchored to the concrete surface by means of "L" shaped mild steel shear key welded with existing reinforcement including the cost of materials, labour, tool & plants as approved by Engineer- in-charge. | 5.2 | sqm Total | |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

Ref No - DAV-HA-296

Date - 10.11.2022

ABSTRACT OF COST OF CONSTRUCTING PARTITION WALL, OPENING DOOR AND WINDOW IN FEE OFFICE AT D.A.V. PUBLIC SCHOOL, AURANGABAD, BIHAR

| S.NO | S.O.R | DESCRIPTION | Qty. | Rate | UNIT | Amount |
|------|---------|--|------|------|------|--------|
| | | CLOSING AND PLASTERING EXISTING WINDOW AND OPENINGS | | | | |
| 1 | 15.7.4 | Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead: In cement mortar | 12 | | each | |
| | | CONSTRUCTION OF NEW PARTITION | | | | |
| | | WALL | | | | |
| 2 | 2.8.1 | Earth work in excavation in foundation trenches or drains(not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All Kinds of soil | 1.1 | | Cu m | |
| 3 | 2.28 | Supplying and filling in plinth with Local sand including watering, ramming, consolidating and dressing complete | 0.4 | | Cu m | |
| 4 | 11.72 | Providing designation 100A one brick flat soling joints filled with local sand complete | 1.8 | | Sq m | |
| 5 | 5.1.3 | Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring,shuttering,finishing and reinforcement-All work puto plinth level 1:2:4 (1 cement:2 coarse sand:4 graded stone aggregate 20 rr.m nominal size) Reinforcement for R.C.C. work including | 0.4 | | | |
| 6 | 5.22 | Reinforcement for R.C.C. Work including straightening, cutting, bending, placing in position and binding all complete. | | | | |
| | 5.22.7D | Thermo-Mechanically Treated bars TMT Fe-500-I6mrn dia. | 55.8 | | KG | |
| | 5.22.7A | Thermo-Mechanically Treated bars TMTC- 500-8mm dia. | 17.9 | | KG | |
| 7 | 6.1.14A | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1:6 (1 cement: 6 coarse sand) | | | CUM | |
| | 6.3A | Extra for Brick work in superstructure above plinth level upto floor V cum | | | CUM | |
| | | | 5 | | CUM | |
| 8 | 13.11.4 | Cement plaster in course sand 12 mm cement plaster of mix: 1:6(1 cement: 6 coarse sand) | 40.8 | | sqm | |

| | | INTERIOR PAINTING AND FINISH | | | | |
|--|-----------|--|------|------------------------|----------|----------|
| | | (INCLUDING CEILING) | | | | |
| 9 | 13.74 | Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete | 80.9 | | sqm | |
| 10 | 13.80 A.1 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | 80.9 | | sqm | |
| 11 | 13.48.1 | Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications. Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of special primer applied @ 0.75 ltr /10 sqm. | 80.9 | | SqM | 0 |
| | • | FEE COUNTER | | | | |
| 12 | 9.157.1 | Providing and fixing Pre-laminated medium density fibre board IS: 14587:1998 marked, with one side decorative lamination other side balancing lamination Grade-I(exterior grade) in shelves with screws and fittings wherever required, edges to be sealed with PVC edge bending tape 2.00 mm thick of approved brand (fittings to be paid separately). Pre-laminated with decorative lamination one side and other side balancing lamination exterior Grade - I MDF Board 18 mm thick confirming to IS:14587 | 13.0 | | sqm | |
| 13 | NA | ADHESIVE | 8.0 | | kg | |
| | | ELECTRICAL FIXTURES | | | <u>v</u> | |
| 14 NA fixtures like switch board and other miscellaneous charges | | | | lumsum TOTAL | | |
| L | | | | TOTAL | | <u> </u> |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)


Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com


ABSTRACT OF COST FOR WOOD WORK IN EXAMINATION ROOM AT D.A.V PUBLIC SCHOOL, AURANGABAD

Ref no - DAV-HA-294


Date - 10.11.2022


| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|-----|---|----------|--------|------|--------|
| | | SIZE OF CABINET -20' X 2' X11' | | | | |
| 1 | NA | Taking out and carefully dismantling existing cabinet so that it can be assembled again and put to use. | LU | JMPSUM | | |
| 2 | NA | Assembling the pre dismantled cabinet in the new space as per design (inclusive of labour, hinges and adhesive) | 20.4 | | sqm | |
| | | | | TOTAL | | |






LIVODOCED E







ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

Ref No.....

Date.....

ABSTRACT OF COST OF WINDOW CLOSING AND PAINTING IN MAIN HALL AT D A V PUBLIC SCHOOL, AURANGABAD, BIHAR

| S.NO | S.O.R | DESCRIPTION | Qty. | Rate | UNIT | Amount |
|------|---------|--|------|-------|------|--------|
| | | CLOSING AND PLASTERING EXISTING WINDOW AND OPENINGS | | | | |
| 1 | 15.13.2 | Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 meters lead. Of area beyond 3 sqm | 12 | | each | |
| 2 | 6.1.14A | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1:6 (1 cement: 6 coarse sand) | | | CUM | |
| | 6.3A | Extra for Brick work in superstructure above plinth level upto floor V cum | | | CUM | |
| | | | 15 | | CUM | |
| 3 | 13.11.4 | Cement plaster in course sand 12 mm cement plaster of mix: 1:6(1 cement: 6 coarse sand) | 60 | | sqm | |
| | | STAGE BACKGROUND WALL PANEL | | | | |
| 4 | 9.157.1 | Providing and fixing Pre-laminated medium density fibre board IS: 14587:1998 marked, with one side decorative lamination other side balancing lamination Grade-I(exterior grade) in shelves with screws and fittings wherever required, edges to be sealed with PVC edge bending tape 2.00 mm thick of approved brand (fittings to be paid separately). Pre-laminated with decorative lamination one side and other side balancing lamination exterior Grade - I MDF Board 18 mm thick confirming to IS:14587 | 15.0 | | sqm | |
| 5 | NA | ADHESIVE | 8.0 | 250.0 | kg | |

| | | INTERIOR PAINTING AND FINISH | | | | |
|----|-----------|--|------|--------|-----|--|
| | | (INCLUDING CEILING) | | | 7 | |
| 6 | 13.74 | Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete | 450 | | sqm | |
| 7 | 13.80 A.1 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | 450 | | sqm | |
| 8 | 13.48.1 | Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications. Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of special primer applied @ 0.75 ltr /10 sqm. | 450 | | SqM | |
| | | LIGHTING AND FIXTURES | | | | |
| 9 | NA | Diffused light of approximate length (desired colour and brand) (inclusive of wire and fitting | 14.0 | | m | |
| 10 | NA | fixtures like switch board and other miscellaneous charges | | lumsum | | |
| | | | | TOTAL | | |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)


Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF COST FOR FALSE CEILING IN MAIN HALL AT D.A.V PUBLIC SCHOOL, AURANGABAD, BIHAR

Ref no

| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|-------|---|----------|-------|------|--------|
| | | AREA | 2,386.0 | | SQFT | |
| | | FALSE CEILING | 2,386.0 | | SQFT | |
| 1 | 12.82 | Providing and fixing at all height false ceiling of 12.5 mm thick -tapered edge gypsum board conforming to IS : 2095 including - providing and fixing as per specification and mention in SOR. (EXCLUDING PAINTING) | 221.7 | | Sq m | |
| 2 | NA | LED AT LIGHT POINTS (UNIT WISE) (inclusive of wire and wiring) | 42.0 | | each | |
| 3 | NA | Diffused light of approximate length (desired colour and brand) | 111.0 | | m | |
| 4 | NA | Electrical work and fitings per light | 42.0 | | each | |
| 5 | NA | fixtures like switch board and other miscellaneous charges | lumsum | | | |
| | | | | TOTAL | | |





ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

Ref No.....

Date.....

ABSTRACT OF COST OF ALUMINUM WINDOW IN MAIN HALL AT D A V PUBLIC SCHOOL, AURANGABAD, BIHAR

| S.NO | S.O.R | DESCRIPTION | Qty. | Rate | UNIT | Amount |
|------|--------|--|------|-------|------|--------|
| | - | ALUMINUM WINDOW WORK | | - | | |
| 1 | 21.2.2 | Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-chargePre-laminated particle board with decorative lamination on both sides (FOR 2 DOORS) | | | | |
| | | 6' X 9' X 8 | 40.0 | | Sq m | |
| 2 | 21.3.2 | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge . (Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness(weight not less than 12.50 kg/sgm) | 40.0 | | sqm | |
| 3 | N A | Miacellaneous items and other fitting and fixture charge | | L.S | | |
| | | | | TOTAL | | |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar) Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF COST FOR DEMOLITION OF TOILET, FALSE CEILING, FLOORING ALONG WITH WALL FINISHING IN PRINCIPAL'S CHAMBER HALL AT D.A.V PUBLIC SCHOOL, AURANGABAD

Ref no

| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|---------|--|----------|-------|------|--------|
| | | AREA | 476.0 | | SQFT | |
| | | DIMOLISHING TOILET, CLOSING EXISTING WINDOW AND PLASTERING | | | | |
| 1 | 15.7.4 | Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead: In cement mortar | 4 | | CUM | |
| 2 | 15.13.2 | Taking out doors, windows and clerestory window shutters (steel or wood) including stacking within 50 meters lead. Of area beyond 3 sqm | 4 | | each | |
| 3 | 6.1.14A | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1:6 (1 cement: 6 coarse sand) | | | CUM | |
| | 6.3A | Extra for Brick work in superstructure above plinth level upto floor V cum | | | CUM | |
| | | | 1.5 | | CUM | |
| 4 | 13.11.4 | Cement plaster in course sand 12 mm cement plaster of mix: 1:6(1 cement: 6 coarse sand) | 15 | | sqm | |
| | | FALSE CEILING | 476.0 | | SQFT | |
| 5 | 12.82 | Providing and fixing at all height false ceiling of 12.5 mm thick -tapered edge gypsum board conforming to IS : 2095 including - providing and fixing as per specification and mention in SOR. | 44.2 | | Sq m | |
| 6 | NA | LED AT LIGHT POINTS (UNIT WISE) (inclusive of wire and wiring) | 18.0 | | each | |
| 7 | NA | Diffused light of approximate length (desired colour and brand) | 25.0 | | m | |
| 8 | NA | Electrical work and fitings per light | 18.0 | | each | |
| 9 | NA | fixtures like switch board and other miscellaneous charges | | umsum | | |
| | | INTERIOR PAINTING AND FINISH (INCLUDING WALL AND CEILING BOTH) | | | | |

| 10 | 13.74 | Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete | 142 | sqm | |
|----------|-----------|--|-----|--------------|--|
| 11 | 13.80 A.1 | Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete. | 142 | sqm | |
| 12 | 13.48.1 | Finishing with Deluxe Multi surface paint system for interiors and exteriors using Primer as per manufacturers specifications. Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including one coat of special primer applied @ 0.75 ltr /10 sqm. | 142 | SqM | |
| 13 | na | Providing and applying <u>Wall paper</u> of approved colour and brand to enhance certain corners and spaces | 16 | SqM | |
| . | | | | | |
| l | | FLOORING ON DIMOLISHED PORTION | | | |
| 14 | 11.41.2 | FLOORING ON DIMOLISHED PORTION Providing and laying vitrifed floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS : 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching pigments etc., complete. | 4.0 | Sq m | |
| 14 | 11.41.2 | Providing and laying vitrifed floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS : 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching | 4.0 | Sq m Sq M | |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF COST FOR WOOD WORK IN PRINCIPAL'S CHAMBER HALL AT D.A.V PUBLIC SCHOOL, AURANGABAD

Ref no

| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|---------|--|----------|-------|------|--------|
| | | SIZE OF CUPBOARD -15' X 1'6" X 8' | | | | |
| 1 | 9.23A.1 | Providing and fixing 25 mm thick shutters for cupboards etc.including black enamelled M.S. butt hinges with necessary screws : Panelled or panelled and glazed shutters | 14.6 | | sqm | |
| 2 | 9.157.1 | Providing and fixing Pre-laminated medium density fibre board IS: 14587:1998 marked, with one side decorative lamination other side balancing lamination Grade-I(exterior grade) in shelves with screws and fittings wherever required, edges to be sealed with PVC edge bending tape 2.00 mm thick of approved brand (fittings to be paid separately). Pre-laminated with decorative lamination one side and other side balancing lamination exterior Grade - I MDF Board 18 mm thick confirming to IS:14587 | 20.0 | | sqm | |
| 3 | NA | SCREW , BOLTS AND ADHESIVE | LS | | | |
| | | | | TOTAL | | |

ARCHITECTS, ENGINEERS, INTERIOR DESIGNERS

Add:- Near Hindustan Press, Cotton Mill, Gaya - 823001 (Bihar)

Mob. No. 7739269750, 700467722 / Email : happyandassociate@gmail.com, Website : www.happysgroup.com

ABSTRACT OF ESTIMATE FOR CONSTRUCTION OF TOILET FOR PRINCIPAL'S CHAMBER AT DAV PUBLIC SCHOOL, AURANGABAD

Ref no

| Serial | SoR | Particulars | Quantity | Rate | Unit | Amount |
|--------|----------|---|----------|------|--------------|--------|
| | | PRINCIPAL'S CHAMBER | | | | |
| 1 | 2.8.1 | Earth work in excavation in foundation trenches or drains(not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m. All Kinds of soil | 2.3 | | Cu m | |
| 2 | 2.28 | Supplying and filling in plinth with Local sand including watering, ramming, consolidating and dressing complete | 1.8 | | Cu m | |
| 3 | 11.72 | Providing designation 100A one brick flat soling joints filled with local sand complete | 4.4 | | Sq m | |
| 4 | 5.1.3 | Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring,shuttering,finishing and reinforcement-All work puto plinth level 1:2:4 (1 cement:2 coarse sand:4 graded stone aggregate 20 rr,m nominal size) | 1.0 | | | |
| 5 | 4.1.3 | Providing PCC (1:2:4) with graded Stone chips of 20 mm nominal size excluding the cost of centring and shuttering all works in Foundation all complete | 0.5 | | Cu m | |
| 6 | 5.2.3 | Reinforced cement concrete work in wall (any thickness), including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. upt floor five level excluding cost of centring, shuttering, finishin and reinforcement. 1:2:4(1 cement :2 coarse sand:4 graded stone aggregate 20 mm nominal size) | 0.8 | | C <u>u M</u> | |
| 7 | 5.3 | Reinforced cement conrete work in beams,suspended floors, roofs having slope upto 15, landings,balconiec, shelves, chajjas, lintels, bands, plain window sills, staircases and spiral stair cases upto floor five level excludingthe cost of centring, shuttering, finishing and reinforement with 1:2:4(1 cement:2 coarse sand:4 graded stone aggregate 20 mm nominal size). | 1.3 | | Cu M | |
| 8 | 5.22 | Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete. | 382.5 | | KG | |
| | 5.22.7B | Thermo-Mechanically Treated bars TMTC-500- 10mm dia. | | | | |
| 9 | 6.1.12/1 | Brick work with bricks of class designation 100A in foundations and plinth in : Cement mortar 1 .:4 (1 cement: 4 coarse sand) | 4.8 | | Cu m | |
| 10 | 13.11.4 | 12 mm (1:6) cement Plaster (Toilet wall) | 31.0 | | Sq m | |

| 11 | 11.38 | Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of ist quality conforming to IS : 15622 of approved make in colours such shades except white , Ivory , Grey , Fume Red , Brown , laid on 20 mm thick Cement motar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc., complete. | 4.6 | Sq m | |
|----|---------|---|--------|-------|--|
| 12 | 11.36 | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS : 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-charge in skirting, risers of steps and dados over 12 mm thick bed of cement Motar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete. FULL WALL | 29.0 | Sq m | |
| 13 | 13.78.1 | Providing one coat of cement primer of approved brand and manufacture on wall surface all complete | 31.0 | Sq m | |
| 14 | 13.79.1 | Providing water proof cement paint of approved brand and manufacture and of required shade to give and even shade three or more coat on new work all complete | 31.0 | Sq m | |
| 15 | 17.2.1 | W.C. pan with ISI marked white solid plastic seat and lid | 1.0 | EACH | |
| 16 | 17.4.2 | Range of two urinal basins with 5 litre white P.V.C. automatic flushing cistern | 1.0 | EACH | |
| 17 | 17.7.8 | White Vitreous China Surgeon type wash basin of size 660x460 mm with a pair of 15 mm C.P. brass pillar taps with elbow operated levers | 1.0 | EACH | |
| 18 | 18.3.3 | Providing and fixing Polyethelene-Aluminium- Polyethelene (PE-ALPE) Composite Pressure Pipes conforming to IS - 15450, including all special fittings of composite materials 2025 (25 mm OD) pipe | 60.0 | metre | |
| 19 | ΝA | Door | 1.0 | Each | |
| 20 | NA | WB socket | | UMSUM | |
| 21 | NA | light points | | | |
| 22 | N A | geyser of approved brand (providing and fixing) | | UMSUM | |
| 23 | N A | exhaust fan (providing and fixing) | L | UMSUM | |
| 24 | N A | soap holder, towel holder and other miscellaneous accessories | LUMSUM | | |
| 25 | ΝA | Shower,taps etc | LUMSUM | | |
| | | | | Total | |

